

Patch Cord



The Patch Cord has been tested and verified for full compliance with the following standards:

ANSI/TIA/EIA-568-B.2-1 IEC 61156-5 (ISO/IEC 11801 2nd edition) CENELEC EN 50288-3 EN50173:2002, EN50167, EN50169

Applications

The Patch Cord supports all available LAN applications and they are used for work area, jumper and patching in LANs, warranty features until 100 MHz. The Patch Cords are molded. Both cable ends are terminated with modular shielded plug connectors.

General properties

Construction: Stranded bare annealed copper wire

Diameter: 24AWG Insulation: Polyolefin

Number of insulated conductors: 8, twisted in 4 pairs. Color code: Blue x White/Blue, Orange x White/Orange,

Green x White/Green, Brown x White/Brown.
Overall shield: laminated alluminium foil
Drain wire: 24 AWG solid tin-coated copper

Benefits and Features

Exceed Cat.5E requiriments
High quality and cable design
High Return Loss and NEXT Loss values
Low propagation delay
High Electro-Magnetic Interference protection
Confortable cable handling by a smooth jacket
Molded plug terminations.

Electical Characteristics @ 20°C

Contact Resistance: 20 mohm max Input/Output resistance: 200 mohm max

Input/Output resistance Unbalance: 50 mohm max


Voltage rating: 230 Vrms max


Insulation Resistance: 500M?/min @ 500 Vdc

DC Resistance: 0.1 Ohm max

Frequency	Attenuation	NEXT	PSNEXT	ACR	PSACR	ELFEXT	PSELFEXT	RL
MHz	dB/100m	dB	dB	dB/100m	dB/100m	dB/100m	dB/100m	dB
1	2.1	65.3	62.3	63.2	60.2	63.8	60.8	20.0
4	4.1	56.3	53.3	52.2	49.2	51.7	48.7	23.0
10	6.5	50.3	47.3	43.8	40.8	43.8	40.8	25.0
16	8.2	47.3	44.3	39.1	36.1	39.7	36.7	25.0
20	9.3	45.8	42.8	36.5	33.5	37.7	34.7	25.0
31.25	11.7	42.9	39.9	31.2	28.2	33.9	30.9	23.6
62.5	17.0	38.4	35.4	21.4	18.4	27.8	24.8	21.5
100	22.0	35.3	32.3	13.3	10.3	23.8	20.8	20.1
155		32.5	29.5					
200		30.8	27.8	-				Ŷ.







Cod.	DESCRIPTION
E2040-05	FTP CAT.5e 0.5 M
E2040-1	FTP CAT.5e 1M
E2040-2	FTP CAT.5e 2M
E2040-3	FTP CAT.5e 3M
E2040-5	FTP CAT.5e 5M
E2040-10	FTP CAT.5e 10 M

Other sizes available upon request